

XT [5] [5] [5] Series Cryo-Science Technologies





XT Series

The Extended Time Series (XT) of cryogenic refrigerators are designed for long-term storage of a variety of materials at cryogenic temperatures. This series also offers low profile models (XTL), with 5" canisters.







Taylor-Wharton Theodore, AL 1.251.443.8680

Taylor-Wharton Cryogenics Australia Pty. Ltd. 61.2.6040.2533

Taylor-Wharton Asia (M) Sdn Bhd Albury, NSW Selangor Darul Ehsan 60.3.5191.3003



Features

- New Rugged Construction ribbed high strength aluminum body, magniformed necktube design, and more durable paint
- Versatile storage system convenient canister numbered index location ring and tapered internal spider.
- Superior vacuum performance with super insulation
- Security Accessory low-level alarm is available with remote monitor capability.
- Lockable lids
- Mobility Roller bases are available for some models











| Models | | XTL3 | XTL8 | XT10 | XT20 | XT34 |
|---|-----------------|-----------------|-----------------|------------------|------------------|------------------|
| Static Holding Time days (1) | | 27 | 80 | 100 | 230 | 340 |
| Working Time days (2) | | 17 | 50 | 62 | 140 | 212 |
| Evaporation Rate (1) liters/days | | 0.11 | 0.10 | 0.10 | 0.09 | 0.10 |
| Liquid Nitrogen Capacity - liters | | 3 | 8 | 10 | 20.7 | 34 |
| Weight Empty | - lbs. - kg. | 7.2 3.3 | 19.6 8.9 | 16.5 7.5 | 26 11.8 | 34.75 15.8 |
| Weight Full (3) | - lbs. - kg. | 12.5 5.7 | 33.8 15.4 | 34.3 15.6 | 62.8 28.6 | 95.3 43.3 |
| Neck Diameter | - in. - mm. | 2.0 51 | 2.0 51 | 2.0 51 | 2.0 51 | 2.0 51 |
| Overall Height | - in. - mm. | 17.2 437 | 19 483 | 23.8 597 | 25.8 655 | 26.3 668 |
| Overall Diameter | - in. - mm. | 7.6 193 | 15.6 396 | 11.4 290 | 15.6 396 | 18.8 478 |
| Number of Canisters | | 6 | 6 | 6 | 6 | 6 |
| Canister Dimensions (4) | - in. - mm. | 1.5x5 38x127 | 1.5x5 38x127 | 1.5x11 38x279 | 1.5x11 38x279 | 1.5x11 38x279 |
| Number of 1.2 ml & 2.0 ml vials (5/cane) | | NA | NA | 150 | 150 | 150 |
| Number of 1.2 ml & 2.0 ml vials (6/cane) | | NA | NA | 180 | 180 | 180 |
| Number of 1/2 cc straws (10/cane) | | NA | NA | 540 | 540 | 540 |
| Number of 1/2 cc straws - Bulk (1 level) | | 750 | 750 | N/A | N/A | N/A |
| Number of 1/2 cc straws - Bulk (2 levels) | | NA | NA | 1500 | 1500 | 1500 |
| Roller Base | | N/A | R018-8C00 | N/A | R018-8C00 | R033-8C00 |
| Low-Level Alarm | | N/A | N/A | N/A | R033-8C15 | R033-8C15 |

⁽¹⁾ Evaporation rate and static holding time are nominal. Actual rate may be affected by the nature of the contents, atmospheric conditions, container history, and manufacturing tolerances.

⁽²⁾ Work time is an arbitrary, reference-only value to estimate container performance under the actual operating conditions.
(3) Without canisters.
(4) Canisters also available in 5.0 in. (127 mm) height for 10 XT, 20XT and 34XT.